

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed

1.1. Name of the Data, data collection Project, or data-producing Program:

2019 NOAA Bathymetric Lidar with Waveform Metrics: Saipan, CNMI

1.2. Summary description of the data:

This data package contains bathymetric light detection and ranging (lidar) Chiroptera-4X .LAS 1.4 files with waveform metrics (as extra bytes) for 0 to 50 meter depths around the island of Saipan, Commonwealth of the Northern Mariana Islands (CNMI). Bathymetric lidar waveforms depict the amount of laser light returned from the seafloor recorded during each laser pulse. Typically, only the leading edge of the seafloor return is used to calculate bottom depth. However, the shape of the seafloor return also contains novel information about the physical structure and biological cover on the seafloor (Collin et al. 2011, Wilson et al. 2019). To extract this information, the National Oceanic and Atmospheric Administration (NOAA) National Centers for Coastal Ocean Science (NCCOS) partnered with Oregon State University (OSU), NOAA Office for Coastal Management (OCM), Woolpert and Hexagon Leica to develop software to export, process, normalize and rasterize 16 LWFM describing the shape of the seafloor return (Jung et al. In Review; Collin et al. 2011; Parrish et al. 2014; Kashani et al. 2015; Kogut et al. 2022). The resulting LWFM rasters were used to predict the distribution of key coral reef taxa and habitats west of Saipan (Costa et al. 2024). This effort marks one of the few studies that have used LWFM to predict tropical coral reef habitats to date. These processing workflows and associated software will also make LWFM creation easier and more routine for future Chiroptera-4X lidar collections by NOAA and its partners. This project was funded by NOAA's Coral Reef Conservation Program (CRCP), and leverages significant investments made by NOAA NCCOS, NOAA National Geodetic Survey, NOAA Office for Coastal Management, and the U.S. Geological Survey in the region.

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2019-07-11 to 2019-08-21

1.5. Actual or planned geographic coverage of the data:

W: 145.605473, E: 145.837466, N: 15.294146, S: 15.085512

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)
remote-sensing image

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:

1.8.1. If data are from another observing system, please specify:

2. Point of Contact for this Data Management Plan (author or maintainer)

2.1. Name:

NCCOS Scientific Data Coordinator

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

2.4. E-mail address:

NCCOS.data@noaa.gov

2.5. Phone number:

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:

3.2. Title:

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

5. Data Lineage and Quality

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Lineage Statement:

This data was collected by Woolpert, Inc. for the USGS and NOAA Office for Coastal Management (OCM). The LiDAR data was collected for Saipan from 11 Jul to 21 Aug 2019. The bathymetry was georeferenced horizontally to the North American Datum 1983 (NAD83), Universal Transverse Mercator, Zone 55 North (UTM 55N, meters) and vertically to the Northern Marianas Vertical Datum of 2003 (NMVD03, meters) coordinate systems. All lidar data for this project were collected to meet National Geospatial Program Lidar Base Specification Version 1.3 QL1 standard, while simultaneously acquiring bathymetric lidar data at National Coastal Mapping Strategy 1.0 QL2b standard. The Root Mean Square Delta z (RMSDz) was 0.033 for Saipan when comparing adjacent flight lines. For more information, please see NOAA and USGS 2019. Waveform metrics were added by Woolpert, Inc., Oregon State University and NOAA National Centers for Coastal Ocean Science (NCCOS). Data were reduced to geographic coordinates on the ellipsoid for ingest in the Digital Coast by NOAA OCM.

Process Steps:

- All lidar data were acquired using a HE4X sensor (Figure 4). The HE4X is a latest generation topographic and bathymetric lidar sensor. The system provides denser data than previous traditional bathymetric lidar systems. It is unique in its ability to acquire bathymetric lidar, topographic lidar and 4-band digital camera imagery simultaneously. The HE4X provided up to 500 kHz topographic data and an effective 140 kHz shallow bathymetric data and a 40 kHz deep channel. While not a required deliverable for this survey, 4-band 80 MP digital camera imagery was also collected simultaneously with the sensor's RCD-30 camera and utilized during data editing in some cases. The bathymetric and topographic lasers are independent and do not share an optical chain or receivers, so they are optimized for their specific function. As with any bathymetric lidar, maximum depth penetration is a function of water clarity and seabed reflectivity. The HE4X is designed to penetrate to 3 times the secchi depth. This is also represented as $D_{max} = 4/K$, where K is the diffuse attenuation coefficient, and assuming K is between 0.1 and 0.3, a normal sea state and 15% seabed reflectance. Both the topographic and bathymetric sub-systems use a palmer scanner to produce an elliptical scan pattern of laser points with a degree of incidence ranging from +/-14 degrees (front and back) to +/-20 degrees (sides), providing a 40 degree field of view. This has the benefit of

providing multiple look angles on a single pass and helps to eliminate shadowing effects. This can be of particular use in urban areas, where all sides of a building are illuminated, or for bathymetric features such as the sides of narrow water channels, or features on the seafloor such as smaller objects and wrecks. It also assists with penetration in the surf zone where the back scan passes the same ground location a couple of seconds after the front scan, allowing the areas of whitewater to shift.

- Position and orientation data were acquired in the aircraft using a NovAtel SPAN with LCI-100C IMU. All data were post-processed using NovAtel Inertial Explorer software to provide a tightly coupled position and orientation solution. A single base station was used to control trajectory processing providing final trajectories for Saipan and Tinian on NAD83 (MA11), Epoch 2010, located in the Saipan airport. This base station was replaced for each of the three separate collects of the project (Table 11). SPN1, SPN2 and SPN3 were occupied with a Trimble GNSS receiver by Woolpert. Due to the distance of Rota, Aguijan, Farallon de Medinilla, and Pagan from the single base station on Saipan and their remoteness a precise point positioning (PPP) solution was used for them on ITRF2014. To establish a reliable coordinate for SPN1 data were uploaded to the National Geodetic Service (NGS) Online Positioning User Service (OPUS), and for SPN2 and SPN3 Trimble CenterPoint RTX Post-Processing service was used. The average OPUS or RTX coordinate from multiple days of observations was used to process the final trajectories.

- Initial data coverage analysis and quality checks to ensure there were no potential system issues were carried out in the field prior to demobilization of the sensor. Final processing was conducted in Woolpert's offices. In general data were initially processed in Leica's Lidar Survey Studio (LSS) using final processed trajectory information. LAS files from LSS were then imported to a Terrascan project where spatial algorithms were used to remove noise and classify bare earth/ground. Manual review was conducted in both Terrascan and LP360 prior to product creation.

- Lidar processing was conducted using the Leica Lidar Survey Studio (LSS) software. Calibration information, along with processed trajectory information were combined with the raw laser data to create an accurately georeferenced lidar point cloud for the entire survey in LAS v1.4 format. All points from the topographic and bathymetric laser include 16-bit intensity values. During this LSS processing stage, an automatic land/water discrimination is made for the bathymetric waveforms. This allows the bathymetric (green) pulses over water to be automatically refracted for the pulse hitting the water surface and travelling through the water column, producing the correct depth. Another advantage of the automatic land/water discrimination is that it permits calculation of an accurate water surface over smaller areas, allowing simple bathymetric processing of smaller, narrower streams and drainage channels. Sloping water surfaces are also handled correctly. Prior to processing, the hydrographer can adjust waveform sensitivity settings dependent on the environment encountered and enter a value

for the refraction index to be used for bathymetry. The index of refraction is an indication of the water type. Values used for sensitivity settings and the index of refraction are included in the LSS processing settings files. A value of 1.34206 was used for the index of refraction, indicating saltwater. In the field, default waveform sensitivity settings were used for processing. In order to determine the optimal waveform sensitivity settings for final processing, sample areas were selected and processed with multiple different settings, to iteratively converge on the best possible settings. This is done by reviewing the processed point cloud and waveforms within sample areas. Settings affect which waveform peaks are classified as valid seabed, and which peaks are classified as noise. Optimal settings strike a balance between the amount of valid data that is classified as seabed bottom, and the amount of noise that is incorrectly classified due to peaks in the waveforms. Ideally all valid data is selected, while only a small amount of noise remains to be edited out. Once optimal threshold settings were chosen, these were used for the entire project. It is important to note that all digitized waveform peaks are available to be reviewed by the hydrographer; both valid seabed bottom and peaks classed as noise. This allows the hydrographer to review data during TerraScan and LP360 editing for valid data such as objects that may have been misclassified as noise. LSS processing produced LAS files in 1.4 format. Additional QC steps were performed prior to import to TerraScan. Firstly, the derived water surface was reviewed to ensure a water surface was correctly calculated for all bathymetry channels. No significant issues were apparent. Spot checks were also made on the data to ensure the front and back of the scans remained in alignment and no calibration or system issues were apparent prior to further data editing in TerraScan. LSS stores data in multiple LAS files for a single flight line. Each file corresponds to a single .dat file from the raw airborne data. Woolpert merged these multiple files into a single file per flight line and moved data into a standard class definition in preparation for data editing using Woolpert's proprietary scripts within SAFE's FME software. Data produced by LSS for flights over Saipan and Tinian were processed on the NAD83 (MA11) Epoch 2010 datum in UTM 55N Zone with units in meters, and elevations on the ellipsoid also in meters. Data produced for Aguijan and Rota were processed on the ITRF2014 datum in UTM 55N Zone with units in meters, with elevations on the ellipsoid also in meters.

- After data were processed in LSS and the data integrity reviewed, Aguijan, and Rota were transformed from the ITRF2014 ellipsoid to the NAD83 (MA11) Epoch 2010 ellipsoid using VDatum. With the entire project now on the correct ellipsoid, data were organized into tiles within a TerraScan project. The tile layout is the same as that provided with the project deliverables. Data classification and spatial algorithms were applied in Terrasolid's TerraScan software. Customized spatial algorithms, such as isolated points and low point filters, were run to remove gross fliers in the topographic and bathymetric data. A grounding algorithm was also run on the topographic data to distinguish between points representing the bare earth, and other valid topo lidar points representing features such as vegetation, buildings, and so forth. Algorithms were run on the entire dataset. Data were reviewed

manually to reclassify any valid bathy points incorrectly identified by the automated routines in LSS as invalid, and vice versa. In addition, any topo points over the water were reclassified to correct the ground representation. Manual editing was conducted both in TerraScan and LP360. Steps for manual editing included:

- Re-class any topo unclassified laser data and bathy seabed data from the water surface to a water surface class
- Review bathymetry in cross section.
- Re-class suitable data to Seabed (Class 40).
- Re-class any noise in the bathy ground class to bathy noise (Class 45).
- Review bathymetry using imagery and nautical charts and re-class obvious man-made objects to Submerged Object (Class 43).

Once editing was completed in TerraScan the data were vertically transformed to the NMVD03 datum using GEOID12B.

- 2024-01-24 00:00:00 - Data were received by NOAA OCM from NOAA NCCOS in NAD83(MA11) UTM 55N coordinates with the vertical in NMVD03/Geoid12b. Waveform metrics had been added as extra bytes, but no documentation of the process was provided. The projection and geoid model were removed to produce geographic coordinates on the ellipsoid (EPSG:6321) for incorporation into the NOAA Digital Coast to allow custom processing.

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management
- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
 - 7.1.1. If data are not available or has limitations, has a Waiver been filed?
 - 7.1.2. If there are limitations to data access, describe how data are protected
- 7.3. Data access methods or services offered

- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:

6.3. URL of metadata folder or data catalog, if known:

<https://www.fisheries.noaa.gov/inport/item/71943>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:id=10031/details/10031>
<https://noaa-nos-coastal-lidar-pds.s3.amazonaws.com/laz/geoid12b/10031/index.html>

7.3. Data access methods or services offered:

7.4. Approximate delay between data collection and dissemination:

7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

8.1.1. If World Data Center or Other, specify:

8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

National Centers for Coastal Ocean Science - Silver Spring, MD

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.