

Please provide the following information, and submit to the NOAA DM Plan Repository.

### Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

## 1. General Description of Data to be Managed

### 1.1. Name of the Data, data collection Project, or data-producing Program:

2011 Federal Emergency Management Agency (FEMA) Topographic Lidar:  
Massachusetts and Rhode Island

### 1.2. Summary description of the data:

This data set is a combination of 3 separate FEMA collections (Blackstone, Charles-Quincy and Narragansett) with similar specifications. See the Ground Control process step for further information on functional areas. Ground Control is collected throughout the AOI for use in the processing of LiDAR data to ensure data accurately represents the ground surface. QA/QC checkpoints, (FVA and CVA - see Ground Control process step for further information) also collected throughout the AOI, are used for independent quality checks of the processed LiDAR data. LiDAR acquisition products include Pre- and Post-flight reports which contain information on the flightlines, equipment parameters, and other pertinent acquisition details. The LiDAR product itself consists of tiles of LAS points which are partially classified such that the bare earth points can be calibrated to the ground surface and tested via the independent QC to ensure the ground surface is accurately represented.

### 1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

### 1.4. Actual or planned temporal coverage of the data:

2010-12-02 to 2010-12-17

### 1.5. Actual or planned geographic coverage of the data:

W: -71.933732, E: -70.907919, N: 42.457842, S: 41.754609

### 1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)  
las

### 1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys,

*enforcement activities, numerical model, etc.)*

**1.8. If data are from a NOAA Observing System of Record, indicate name of system:**

**1.8.1. If data are from another observing system, please specify:**

**2. Point of Contact for this Data Management Plan (author or maintainer)**

**2.1. Name:**

NOAA Office for Coastal Management (NOAA/OCM)

**2.2. Title:**

Metadata Contact

**2.3. Affiliation or facility:**

NOAA Office for Coastal Management (NOAA/OCM)

**2.4. E-mail address:**

coastal.info@noaa.gov

**2.5. Phone number:**

(843) 740-1202

**3. Responsible Party for Data Management**

*Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.*

**3.1. Name:**

**3.2. Title:**

Data Steward

**4. Resources**

*Programs must identify resources within their own budget for managing the data they produce.*

**4.1. Have resources for management of these data been identified?**

**4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):**

**5. Data Lineage and Quality**

*NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.*

### 5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Process Steps:

- 2011-01-01 00:00:00 - GPS based surveys were utilized to support both processing and testing of LiDAR data within FEMA designated Areas of Interest (AOIs). Geographically distinct ground points were surveyed using GPS technology throughout the AOIs to provide support for three distinct tasks. Task 1 was to provide Vertical Ground Control to support the aerial acquisition and subsequent bare earth model processing. To accomplish this, survey-grade Trimble R-8 GPS receivers were used to collect a series of control points located on open areas, free of excessive or significant slope, and at least 5 meters away from any significant terrain break. Most if not all control points were collected at street/road intersections on bare level pavement. Task 2 was to collect Fundamental Vertical Accuracy (FVA) checkpoints to evaluate the initial quality of the collected point cloud and to ensure that the collected data was satisfactory for further processing to meet FEMA specifications. The FVA points were collected in identical fashion to the Vertical Ground Control Points, but segregated from the point pool to ensure independent quality testing without prior knowledge of FVA locations by the aerial vendor.

- 2011-01-01 00:00:00 - Task 3 was to collect Consolidated Vertical Accuracy (CVA) checkpoints to allow vertical testing of the bare-earth processed LiDAR data in different classes of land cover, including: Open (pavement, open dirt, short grass), High Grass and Crops, Brush and Low Trees, Forest, Urban. CVA points were collected in similar fashion as Control and FVA points with emphasis on establishing point locations within the predominant land cover classes within each AOI or Functional AOI Group. In order to successfully collect the Forest land cover class, it was necessary to establish a Backsight and Initial Point with the R8 receiver, and then employ a Nikon Total Station to observe a retroreflective prism stationed under tree canopy. This was necessary due to the reduced GPS performance and degradation of signal under tree canopy. The R-8 receivers were equipped with cellular modems to receive real-time correction signals from the Keystone Precision Virtual Reference Station (VRS) network encompassing the Region 1 AOIs. Use of the VRS network allowed rapid collection times (~3 minutes/point) at 2.54 cm (1 inch) initial accuracy. All points collected were below the 8cm specification for testing 24cm, Highest category LiDAR data. To ensure valid in-field collections, an NGS monument with suitable vertical reporting was measured using the same equipment and procedures used for Control, FVA and CVA points on a daily basis. The measurement was compared to the NGS published values to ensure that the GPS collection schema was producing valid data and as a physical proof point of quality of collection. Those monument measurements are summarized in the Accuracy report included in the data delivered to FEMA. In order to meet FEMA budgetary requirements, AOIs were consolidated into Functional Groups: if AOIs were contiguous, they were treated as one large AOI to allow collection of 20 FVA

points and 15 additional CVA points across the group of AOIs. 20 FVA points are necessary to allow testing to CE95 as 1 point out of 20 may fail vertical testing and still allow the entire dataset to meet 95% accuracy requirements. In similar fashion, 20 CVA points are necessary to test to CE95 as discussed above. 15 CVA points were collected per AOI or per Functional Group with the intention at the outset that 5 of the collected FVAs would perform double-duty as Open-class CVA points, to total 20 CVAs per AOI or Functional Group. The Functional Groups are as follows:

Narragansett/Charles/Blackstone(northeast), Nashua, Blackstone(north and west), Quinnipiac, Quincy/Suffolk (while included as part of the FEMA Charles AOI, was physically separated from the Charles AOI polygon and treated as an independent functional area). The following software packages and utilities were used to control the GPS receiver in the field during data collection, and then ingest and export the collected GPS data for all points: Trimble Survey Controller, Trimble Pathfinder Office. The following software utilities were used to translate the collected Latitude/Longitude Decimal Degree HAE GPS data for all points into Latitude/Longitude Degrees/Minutes/Seconds for checking the collected monument data against the published NGS Datasheet Lat/Long DMS values and into UTM NAD83 Northings/Eastings: U.S. Army Corps of Engineers CorpsCon, National Geodetic Survey Geoid09NAVD88. MSL values were determined using the most recent NGS-approved geoid model to generate geoid separation values for each Lat/Long coordinate pair. In this fashion, Orthometric heights were determined for each Control, FVA and CVA point by subtracting the generated Geoid Separation value from the Ellipsoidal Height (HAE) for publication and use as MSL NAVD88(09).

- 2011-01-01 00:00:00 - Applanix software was used in the post processing of the airborne GPS and inertial data that is critical to the positioning and orientation of the sensor during all flights. POSPac MMS provides the smoothed best estimate of trajectory (SBET) that is necessary for Optech's post processor to develop the point cloud from the LiDAR missions. The point cloud is the mathematical three dimensional collection of all returns from all laser pulses as determined from the aerial mission. Optech's DASHMap software and Leica's ALS Post Processor software were used to create the Raw LIDAR Flight Line strips. At this point this data is ready for analysis, classification, and filtering to generate a bare earth surface model in which the above ground features are removed from the data set. The GeoCue and TerraScan software packages are then used for the automated data classification. Project specific macros are created to classify the ground and to remove the side overlap between parallel flight lines. LAS Class 2 (Ground) is used to check the surveyed control points against the Triangulated LIDAR surface. Any bias is then removed using macro functionality within TerraScan. Unclassified Point Cloud tiles are then created using TerraScan macro functionality. These tiles are populated within GeoCue to ensure correct LAS versioning and LAS Header information. LAS Class 2 is used to check the independent QC points against the Triangulated LiDAR surface. If RMSE is not within guidelines TerraScan software is utilized to remove any bias, and the check is performed again.

- 2013-09-01 00:00:00 - The NOAA Office for Coastal Management (OCM) received the

topographic files in LAS V1.2 format. The files contained lidar elevation measurements, classifications, intensity data, return information, GPS time and scan angle. The data were received in NAD83 UTM Zone 19N and were vertically referenced to NAVD88 using the Geoid09 model. The vertical units of the data were meters. OCM performed the following processing for data storage and Digital Coast provisioning purposes: 1. All Class 11 points were changed to Class 12 (Overlap) 2. The topographic las files' global encoding bit was set to '1' to reflect the use of Adjusted Standard GPS Time. 3. The topographic las files were converted from a Projected Coordinate System (UTM19N) to Geographic coordinates (NAD83). 4. The topographic las files' horizontal units were converted from meters to decimal degrees. 5. The topographic las files were converted from orthometric (NAVD88) heights to ellipsoidal heights using Geoid09.

**5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:**

**5.2. Quality control procedures employed (describe or provide URL of description):**

## 6. Data Documentation

*The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.*

**6.1. Does metadata comply with EDMC Data Documentation directive?**

No

**6.1.1. If metadata are non-existent or non-compliant, please explain:**

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management
- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
- 7.1.1. If data are not available or has limitations, has a Waiver been filed?
- 7.1.2. If there are limitations to data access, describe how data are protected
- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

**6.2. Name of organization or facility providing metadata hosting:**

NMFS Office of Science and Technology

**6.2.1. If service is needed for metadata hosting, please indicate:****6.3. URL of metadata folder or data catalog, if known:**

<https://www.fisheries.noaa.gov/inport/item/49842>

**6.4. Process for producing and maintaining metadata**

*(describe or provide URL of description):*

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: [https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC\\_PD-Data\\_Documentation\\_v1.pdf](https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf)

**7. Data Access**

*NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.*

**7.1. Do these data comply with the Data Access directive?**

**7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?**

**7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:**

**7.2. Name of organization of facility providing data access:**

NOAA Office for Coastal Management (NOAA/OCM)

**7.2.1. If data hosting service is needed, please indicate:****7.2.2. URL of data access service, if known:**

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=2557>

<https://noaa-nos-coastal-lidar-pds.s3.amazonaws.com/laz/geoid18/2557/index.html>

**7.3. Data access methods or services offered:**

This data can be obtained on-line at the following URL:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=2557>

**7.4. Approximate delay between data collection and dissemination:**

**7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:**

**8. Data Preservation and Protection**

*The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.*

**8.1. Actual or planned long-term data archive location:**

*(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)*

**8.1.1. If World Data Center or Other, specify:**

**8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:**

**8.2. Data storage facility prior to being sent to an archive facility (if any):**

Office for Coastal Management - Charleston, SC

**8.3. Approximate delay between data collection and submission to an archive facility:****8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?**

*Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection*

**9. Additional Line Office or Staff Office Questions**

*Line and Staff Offices may extend this template by inserting additional questions in this section.*