

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed

1.1. Name of the Data, data collection Project, or data-producing Program:

2006 FEMA New Jersey Flood Mitigation Lidar: Middlesex County

1.2. Summary description of the data:

LIDAR data is remotely sensed high-resolution elevation data collected by an airborne collection platform. By positioning laser range

finding with the use of 1 second GPS with 100hz inertial measurement unit corrections Terrapoint's LIDAR instruments are able to make

highly detailed geospatial elevation products of the ground, man-made structures and vegetation. The LiDAR flightlines for this project

were planned for a 50% acquisition overlap. The nominal resolution of this project without overlap is 1.37m spacing, but effectively is

2.74m with overlap factored. Four returns were recorded for each pulse in addition to an intensity value. GPS Week Time, Flightline number

and scan angle attributes were provided for each LiDAR point. Data is provided as random points, in LAS v1.0 format, classified according

to ASPRS Class Code 1= Undefined, 2=Ground.

Original contact information:

Contact Name: Claude Vickers

Contact Org: Terrapoint USA

Title: Production Manager

Phone: 1-877-80-TERRA

Email: claude.vickers@terrapoint.com

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2006-10-08 to 2006-10-11

1.5. Actual or planned geographic coverage of the data:

W: -74.632358, E: -74.201558, N: 40.610366, S: 40.249866

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:**1.8.1. If data are from another observing system, please specify:****2. Point of Contact for this Data Management Plan (author or maintainer)****2.1. Name:**

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:**3.2. Title:**

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

5. Data Lineage and Quality

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Process Steps:

- 2006-10-01 00:00:00 - -General Overview: The Airborne LiDAR survey was conducted using an OPTECH 3100EA flying at a nominal height of 1550 meters AGL with a total angular coverage of 40 degrees. Flight line spacing was nominally 564 meters, providing overlap of 50% on adjacent flight lines. All of the lines were flown in a north/south direction for the project. -Aircraft A Piper Navajo, registration C-GPJT, was used for the survey. This aircraft has a flight range of approximately 4.5 hours and was flown at an average altitude of 1550 meters AGL (Above Ground Level), thereby encountering flying altitudes of approximately 1550 meters above Mean Sea Level (MSL). The aircraft was staged from the Linden, NJ Airport, and ferried daily to the project site for flight operations. -GPS Receivers A combination of Sokkia GSR 2600 and NovAtel DL-4+ dual frequency GPS receivers were used to support the airborne operations of this survey and to establish the GPS control network. -Number of Flights and Flight Lines A total of 4 missions were flown for this project with flight times ranging approximately 16.25 hours under good meteorological and GPS conditions. 55 flight lines were flown over the project area to provide complete coverage. Lines were flown at 564 meter spacing to achieve 50% lateral overlap.

- 2006-11-01 00:00:00 - -Airborne GPS Kinematic Airborne GPS kinematic data was processed on-site using GrafNav kinematic On-The-Fly (OTF) software. Flights were flown with a minimum of 6 satellites in view (13 degrees above the horizon) and with a PDOP of better than 4.5. Distances from base station to aircraft were kept to a maximum of 35 km, to ensure a strong OTF (On-The-Fly) solution. For all flights, the GPS data can be classified as excellent, with GPS residuals of 5 cm average but no larger than 8 cm being recorded. -Calculation of 3D laser points (raw data) The post-processing software o derive X,Y,Z values from roll, pitch, yaw and range is Optech' s Realm. -Classification and Editing The data was processed using the software TerraScan, and following the methodology described herein. The initial step is the setup of the TerraScan project, which is done by importing client provided tile boundary index encompassing the entire project areas. The 3D laser point clouds, in

binary format, were imported into the TerraScan project and divided in 425 tiles, as per the contract specifications. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine removes any obvious outliers from the dataset following which the ground layer is extracted from the point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model. This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption is that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within an iteration. A critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model. The data is then manually quality controlled with the use of hillshading, cross-sections and profiles. Any points found to be of class vegetation, building or error during the quality control process, are removed from the ground model and placed on the appropriate layer. An integrity check is also performed simultaneously to verify that ground features such as rock cuts, elevated roads and crests are present. Once data has been cleaned and complete, it is then reviewed by a supervisor via manual inspection and through the use of a hillshade mosaic of the entire project area. -Projection Transformation The data was processed in the native UTM zone in meters and then transformed to the New Jersey State Plane final projection system and US survey feet using an in-house transformation software which utilizes Corpcon DLL.

- 2010-09-25 00:00:00 - The NOAA Office for Coastal Management (OCM) received the files in las format. The files contained Lidar elevation and intensity measurements. The data were in projected in New Jersey State Plane (NAD83) coordinates, and referenced to the orthometric datum NAVD88 using Geoid 03. OCM performed the following processing to the data to make it available within the Digital Coast: 1. The data were converted from New Jersey State Plane (NAD83) coordinates to geographic coordinates (NAD83). 2. The data were converted from NAVD88 (orthometric) heights to GRS80 (ellipsoid) heights using Geoid 03. 3. The LAS data were sorted by latitude and the headers were updated.

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented,

specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.6. Type(s) of data
- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management
- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
- 7.1.1. If data are not available or has limitations, has a Waiver been filed?
- 7.1.2. If there are limitations to data access, describe how data are protected
- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:

6.3. URL of metadata folder or data catalog, if known:

<https://www.fisheries.noaa.gov/inport/item/49855>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted

to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=549>

<https://noaa-nos-coastal-lidar-pds.s3.amazonaws.com/laz/geoid18/549/index.html>

7.3. Data access methods or services offered:

This data can be obtained on-line at the following URL: <https://coast.noaa.gov/dataviewer/>;

7.4. Approximate delay between data collection and dissemination:

7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

8.1.1. If World Data Center or Other, specify:

8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.