

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed

1.1. Name of the Data, data collection Project, or data-producing Program:

2015-2017 USGS Puerto Rico Lidar

1.2. Summary description of the data:

Leading Edge Geomatics (LEG) collected 3451 square miles in Puerto Rico. The nominal pulse spacing for this project was 1 point every 0.7 meters. Dewberry used proprietary procedures to classify the LAS according to project specifications: 0-Never Classified, 1-Unclassified, 2-Ground, 7-Low Noise, 9-Water, 10-Ignored Ground due to breakline proximity, 17-Bridges, 18-High Noise. Dewberry produced 3D breaklines and combined these with the final lidar data to produce seamless hydro flattened DEMs for the project area. The data was formatted according to the USNG tile naming convention with each tile covering an area of 1,500 meters by 1,500 meters. A total of 4,714 tiles were produced for the entire Puerto Rico project. An interim delivery was submitted to USGS in December 2016. There are 2,048 tiles in the tile grid, 1,995 LAS files, and 1,941 DEMs included in this second delivery. The discrepancy between the tile count and the LAS/DEM files is because several tiles cover only open water.

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2015-09-19 to 2017-03-16

1.5. Actual or planned geographic coverage of the data:

W: -67.955, E: -65.213031, N: 18.519065, S: 17.87848

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)
Lidar Point Cloud

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:**1.8.1. If data are from another observing system, please specify:****2. Point of Contact for this Data Management Plan (author or maintainer)****2.1. Name:**

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:**3.2. Title:**

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?**4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):****5. Data Lineage and Quality**

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly

accessible

(describe or provide URL of description):

Process Steps:

- 2017-10-01 00:00:00 - Data for the Puerto Rico Lidar project was acquired by Leading Edge Geomatics, Inc (LEG). The project area included approximately 3,451 contiguous square miles or 8,938 square kilometers for Puerto Rico and smaller municipal islands. Lidar sensor data were collected with the Riegl 680i and Riegl 780 lidar systems. The data was delivered in the Puerto Rico State Plane coordinate system, meters, horizontal datum NAD83 (2011), vertical datum PRVD02, Geoid 12B. The lidar data were acquired over two different acquisition campaigns. The first campaign occurred from January 26, 2016 through May 15, 2016 and acquired two thousand three hundred sixteen (2,316) square miles of topographic lidar data. The second campaign occurred from December 8, 2016 through March 16, 2017 and acquired one thousand seven hundred seventy nine (1,779) square miles of topographic lidar data. Deliverables for the project included a raw (unclassified) calibrated lidar point cloud, survey control, and a final acquisition/calibration report. The calibration process considered all errors inherent with the equipment including errors in GPS, IMU, and sensor specific parameters. Adjustments were made to achieve a flight line to flight line data match (relative calibration) and subsequently adjusted to control for absolute accuracy. Process steps to achieve this are as follows: Rigorous lidar calibration: all sources of error such as the sensor's ranging and torsion parameters, atmospheric variables, GPS conditions, and IMU offsets were analyzed and removed to the highest level possible. This method addresses all errors, both vertical and horizontal in nature. Ranging, atmospheric variables, and GPS conditions affect the vertical position of the surface, whereas IMU offsets and torsion parameters affect the data horizontally. The horizontal accuracy is proven through repeatability: when the position of features remains constant no matter what direction the plane was flying and no matter where the feature is positioned within the swath, relative horizontal accuracy is achieved. Absolute horizontal accuracy is achieved through the use of differential GPS with base lines shorter than 25 miles. The base station is set at a temporary monument that is 'tied-in' to the CORS network. The same position is used for every lift, ensuring that any errors in its position will affect all data equally and can therefore be removed equally. Vertical accuracy is achieved through the adjustment to ground control survey points within the finished product. Although the base station has absolute vertical accuracy, adjustments to sensor parameters introduces vertical error that must be normalized in the final (mean) adjustment. The withheld and overlap bits are set and all headers, appropriate point data records, and variable length records, including spatial reference information, are updated in GeoCue software and then verified using proprietary Dewberry tools.
- 2017-11-01 00:00:00 - Dewberry utilizes a variety of software suites for inventory management, classification, and data processing. All lidar related processes begin by importing the data into the GeoCue task management software. The swath data is tiled according to project specifications (1,500 m x 1,500 m). The tiled data is then

opened in Terrascan where Dewberry classifies edge of flight line points that may be geometrically unusable with the withheld bit. These points are separated from the main point cloud so that they are not used in the ground algorithms. Overage points are then identified with the overlap bit. Dewberry then uses proprietary ground classification routines to remove any non-ground points and generate an accurate ground surface. The ground routine consists of three main parameters (building size, iteration angle, and iteration distance); by adjusting these parameters and running several iterations of this routine an initial ground surface is developed. The building size parameter sets a roaming window size. Each tile is loaded with neighboring points from adjacent tiles and the routine classifies the data section by section based on this roaming window size. The second most important parameter is the maximum terrain angle, which sets the highest allowed terrain angle within the model. As part of the ground routine, low noise points are classified to class 7 and high noise points are classified to class 18. Once the ground routine has been completed, bridge decks are classified to class 17 using bridge breaklines compiled by Dewberry. A manual quality control routine is then performed using hillshades, cross-sections, and profiles within the Terrasolid software suite. After this QC step, a peer review is performed on all tiles and a supervisor manual inspection is completed on a percentage of the classified tiles based on the project size and variability of the terrain. After the ground classification and bridge deck corrections are completed, the dataset is processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydrographic features. The water classification routine selects ground points within the breakline polygons and automatically classifies them as class 9, water. During this water classification routine, points that are within 1x NPS or less of the hydrographic features are moved to class 10, an ignored ground due to breakline proximity. A final QC is performed on the data. All headers, appropriate point data records, and variable length records, including spatial reference information, are updated in GeoCue software and then verified using proprietary Dewberry tools. The data was classified as follows: Class 1 = Unclassified. This class includes vegetation, buildings, noise etc. Class 2 = Ground Class 7= Low Noise Class 9 = Water Class 10 = Ignored Ground due to breakline proximity Class 17 = Bridge Decks Class 18 = High Noise The LAS header information was verified to contain the following: Class (Integer) Adjusted GPS Time (0.0001 seconds) Easting (0.003 m) Northing (0.003 m) Elevation (0.003 m) Echo Number (Integer) Echo (Integer) Intensity (16 bit integer) Flight Line (Integer) Scan Angle (degree)

- 2018-11-14 00:00:00 - Data were obtained via ftp from USGS. Data were converted from Puerto Rico state plane to geographic coordinates and the geoid12b model was removed to obtain ellipsoid heights. The data was then ingested into the Digital Coast Data Access Viewer.

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):**6. Data Documentation**

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management
- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
 - 7.1.1. If data are not available or has limitations, has a Waiver been filed?
 - 7.1.2. If there are limitations to data access, describe how data are protected
- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:**6.3. URL of metadata folder or data catalog, if known:**

<https://www.fisheries.noaa.gov/inport/item/54852>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is

explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=8630>

<https://noaa-nos-coastal-lidar-pds.s3.amazonaws.com/laz/geoid18/8630/index.html>

7.3. Data access methods or services offered:

Data is available online for custom downloads

7.4. Approximate delay between data collection and dissemination:

7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

8.1.1. If World Data Center or Other, specify:

8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.