

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed

1.1. Name of the Data, data collection Project, or data-producing Program:

2017 USFS Lidar: Willamette National Forest - Oakridge, OR

1.2. Summary description of the data:

No metadata record for this data set was provided to the NOAA Office for Coastal Management (OCM). This record was created with information from the data report. A link to the data report is provided in the URL section of this metadata record.

The United States Forest Service, Region 6, (USFS) required leaf-on airborne LiDAR surveys to be collected over of national forestry in Oregon and Washington State. The following areas were requested to be covered: Gifford Pinchot National Forest (GIP) in Vancouver, Washington; Okanogan-Wenatchee National Forest (OKA) in Wenatchee, Washington; Malheur National Forest (MAL) in John Day, Oregon; Deschutes National Forest (DES) in Bend, Oregon, Willamette National Forest (WIL) in Eugene, Oregon, Umpqua National Forest (UMP) in Douglas, Lane, and Jackson Counties, Oregon. The following report applies to the Willamette AOI, which encompasses ten (10) square miles of the Willamette National Forest in Oregon.

Aerial LiDAR data for this task order was planned, acquired, processed and produced at an aggregate nominal pulse spacing (ANPS) of 0.35 meters and aggregate nominal pulse density of 8 pulses per square meter.

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2017-07-15

1.5. Actual or planned geographic coverage of the data:

W: -122.6261, E: -122.5295, N: 43.7844, S: 43.7064

Willamette National Forest project area.

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)

Point Cloud (Digital)

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:

1.8.1. If data are from another observing system, please specify:

2. Point of Contact for this Data Management Plan (author or maintainer)

2.1. Name:

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:

3.2. Title:

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

Yes

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

Unknown

5. Data Lineage and Quality

NOAA has issued *Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates*.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Lineage Statement:

The Atlantic Group, LLC collected Light Detection and Ranging (LIDAR) data in the Willamette National Forest project area for the USDA Forest Service. NOAA OCM received the data and ingested it into the Digital Coast Data Access Viewer for distribution.

Process Steps:

- 2017-07-20 00:00:00 - Acquisition Atlantic operated a Leica ALS70-HP LiDAR system on a Cessna (N732JE) during July 15, 2017 for the project area. Atlantic acquired 10 passes of the AOI as a series of perpendicular and/or adjacent flight-lines executed in 1 flight mission. Onboard differential Global Navigation Satellite System (GNSS) unit(s) recorded sample aircraft positions at 2 hertz (Hz) or more frequency. LiDAR data was only acquired when a minimum of six (6) satellites were in view. Two Continuously Operating Reference Stations (CORS) were used to control the LiDAR acquisition for the defined project area.
- 2018-01-01 00:00:00 - Calibration/Classification Atlantic used Leica software products to download the IPAS ABGNSS/IMU data and raw laser scan files from the airborne system. Waypoint Inertial Explorer is used to extract the raw IPAS ABGNSS/IMU data, which is further processed in combination with controlled base stations to provide the final Smoothed Best Estimate Trajectory (SBET) for each mission. The SBETs are combined with the raw laser scan files to export the LiDAR ASCII Standard (*.las) formatted swath point clouds. Departures from planarity of first returns within single swaths in non-vegetated areas were assessed at multiple locations with hard surface areas (parking lots or large rooftops) inside the project area. Each area was evaluated using signed difference rasters (maximum elevation – minimum elevation) at a cell size equal to 2 x ANPS, rounded to the next integer. Using a combination of GeoCue, TerraScan and TerraMatch; overlapping swath point clouds are corrected for any orientation or linear deviations to obtain the best fit swath-to-swath calibration. Relative calibration was evaluated using advanced plane-matching analysis and parameter corrections derived. This process was repeated interactively until residual errors between overlapping swaths, across all project missions, was reduced to ≤ 2 cm. A final analysis of the calibrated lidar is preformed using a TerraMatch tie line report for an overall statistical model of the project area. Individual control point assessments for this project can be found in Section VI of the report. Upon completion of the data calibration, a complete set of elevation difference intensity rasters (dZ Orthos) are produced. A user-defined color ramp is applied depicting the offsets between overlapping swaths based on

project specifications. The dZ orthos provide an opportunity to review the data calibration in a qualitative manner. Atlantic assigns green to all offset values that fall below the required RMSDz requirement of the project. A yellow color is assigned for offsets that fall between the RMSDz value and 1.5x of that value. Finally, red values are assigned to all values that fall beyond 1.5x of the RMSDz requirements of the project. Multiple automated filtering routines are applied to the calibrated LiDAR point cloud identifying and extracting bare-earth and above ground features. GeoCue, TerraScan, and TerraModeler software was used for the initial batch processing, visual inspection and any manual editing of the LiDAR point clouds.

- 2020-05-04 00:00:00 - The NOAA Office for Coastal Management (OCM) received 24 lidar point cloud files in laz format from the USDA Forest Service. The files contained lidar elevation and intensity measurements. The data were in Albers NAD83 Forest Service Region 6, meters, coordinates and NAVD88 (Geoid12B) elevations in meters. The data were classified as: 1-Unclassified, 2-Ground, 7 - Low Noise, 18 - High Noise. OCM processed all classifications of points to the Digital Coast Data Access Viewer (DAV). Classes available on the DAV are: 1, 2, 7, 18. OCM performed the following processing on the data for Digital Coast storage and provisioning purposes: 1. An internal OCM script was run to check the number of points by classification and by flight ID and the gps and intensity ranges. 2. Internal OCM scripts were run on the laz files to convert from orthometric (NAVD88) elevations to ellipsoid elevations using the Geoid 12B model, to convert from Albers NAD83 Forest Service Region 6 coordinates in meters, to geographic coordinates, to assign the geokeys, to sort the data by gps time, and zip the data to database and to http. (Citation: processed lidar data)

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management

- 5.2. Quality control procedures employed
- 7.1.1. If data are not available or has limitations, has a Waiver been filed?
- 7.4. Approximate delay between data collection and dissemination
- 8.3. Approximate delay between data collection and submission to an archive facility

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:

6.3. URL of metadata folder or data catalog, if known:

<https://www.fisheries.noaa.gov/inport/item/59500>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

Yes

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=9080>

https://coast.noaa.gov/htdata/lidar1_z/geoid18/data/9080

7.3. Data access methods or services offered:

Data is available online for bulk and custom downloads.

7.4. Approximate delay between data collection and dissemination:

7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

NCEI_CO

8.1.1. If World Data Center or Other, specify:

8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

Data is backed up to tape and to cloud storage.

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.