

*Please provide the following information, and submit to the NOAA DM Plan Repository.*

**Reference to Master DM Plan (if applicable)**

*As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.*

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

**1. General Description of Data to be Managed****1.1. Name of the Data, data collection Project, or data-producing Program:**

2021 USGS Topobathy Lidar: McKenzie River Corridor, OR

**1.2. Summary description of the data:**

Product: Classified LAS 1.4 files, formatted to 215 individual 3000ft x 3000ft tiles covering the McKenzie River Corridor Topobathymetric Lidar project area.

Geographic Extent: This dataset and derived products encompass an area covering approximately 8,216 Acres of McKenzie River.

Dataset Description: The McKenzie River Corridor Topobathymetric Lidar project called for the planning, acquisition, and processing of Topobathymetric Lidar data collected to Quality Level 1 (QL1) standards. Project specifications are based on the Geological Survey National Geospatial Program Lidar Base Specification, 2020 Revision A. The data was developed based on the NAD83 2011 horizontal datum and the NAVD88 Geoid 18 vertical datum. Data was projected in Oregon Statewide Lambert Conformal Conic. Lidar data was delivered as calibrated and classified LAS 1.4 files. Non-Vegetated Vertical Accuracy (NVA) was assessed using 23 check points located on bare earth in clear, unobstructed areas. Submerged Topography accuracy was assessed using 174 check points collected as feasible in depths up to 1m. Vegetated Vertical Accuracy (VVA) was assessed using 12 check points in Shrub, Forest, Tall Grass landcover types. Single swath nominal pulse spacing (NPS) was designed to be 0.35 at nadir. Aggregate Nominal Pulse Spacing (ANPS) was calculated to be 0.17 using all valid first return points. Derived products include: Topbathymetric Digital Elevation Models (DEMs), Topobathymetric Bare Earth Digital Elevation Models (DEMs), Highest Hit Digital Surface Models (DSMs), 2D waters edge breaklines, and a bathymetric coverage shape.

Ground Condition: Ground condition was free of snow and acquisition occurred free of smoke, fog and cloud cover.

The NOAA Office for Coastal Management (OCM) downloaded 215 laz files from this USGS site and processed the data to the Data Access Viewer (DAV): [https://rockyweb.usgs.gov/vdelivery/Datasets/Staged/Elevation/LPC/Projects/OR\\_McKenzieRiverCorridor\\_Topobathy\\_2021\\_D21/OR\\_MKRC\\_Topobathy\\_2021/LAZ/](https://rockyweb.usgs.gov/vdelivery/Datasets/Staged/Elevation/LPC/Projects/OR_McKenzieRiverCorridor_Topobathy_2021_D21/OR_MKRC_Topobathy_2021/LAZ/)

**1.3. Is this a one-time data collection, or an ongoing series of measurements?**

One-time data collection

**1.4. Actual or planned temporal coverage of the data:**

2021-07-26 to 2021-07-28

**1.5. Actual or planned geographic coverage of the data:**

W: -123.127961, E: -122.034221, N: 44.273376, S: 44.04551

**1.6. Type(s) of data:**

*(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)*

Model (digital)

**1.7. Data collection method(s):**

*(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)*

**1.8. If data are from a NOAA Observing System of Record, indicate name of system:****1.8.1. If data are from another observing system, please specify:****2. Point of Contact for this Data Management Plan (author or maintainer)****2.1. Name:**

NOAA Office for Coastal Management (NOAA/OCM)

**2.2. Title:**

Metadata Contact

**2.3. Affiliation or facility:**

NOAA Office for Coastal Management (NOAA/OCM)

**2.4. E-mail address:**

coastal.info@noaa.gov

**2.5. Phone number:**

(843) 740-1202

**3. Responsible Party for Data Management**

*Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.*

**3.1. Name:****3.2. Title:**

Data Steward

#### 4. Resources

*Programs must identify resources within their own budget for managing the data they produce.*

**4.1. Have resources for management of these data been identified?**

Yes

**4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):**

Unknown

#### 5. Data Lineage and Quality

*NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.*

**5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible**

*(describe or provide URL of description):*

Lineage Statement:

The NOAA Office for Coastal Management (OCM) downloaded the laz data from the USGS rockyweb https site and processed it to be available for custom download from the Data Access Viewer (DAV).

Process Steps:

- 2022-01-07 00:00:00 - Lidar Pre-Processing: 1. Review flight lines and data to ensure complete coverage of the study area and positional accuracy of the laser points. 2. Resolve kinematic corrections for aircraft position data using kinematic aircraft GPS and static ground GPS data. 3. Develop a smoothed best estimate of trajectory (SBET) file that blends post-processed aircraft position with sensor head position and attitude recorded throughout the survey. 4. Calculate laser point position by associating SBET position to each laser point return time, scan angle, intensity, etc. Create raw laser point cloud data for the entire survey in \*.las format. Convert data to orthometric elevations by applying a Geoid 18 correction. 5. Apply refraction correct to bathymetric returns by flightline. 6. Import raw laser points into manageable blocks to perform manual relative accuracy calibration and filter erroneous points. Classify ground points for individual flight lines. 7. Using ground classified points per each flight line, test the relative accuracy. Perform automated line-to-line calibrations for system attitude parameters (pitch, roll, heading), mirror flex (scale) and GPS/IMU drift. Calculate calibrations on ground classified points from paired flight lines and apply results to all points in a flight line. Use every flight line for relative accuracy calibration. 8. Adjust the point cloud by comparing ground classified points to supplemental ground control points.
- 2022-01-07 00:00:00 - Lidar Post-Processing: 1. Classify data to ground and other client designated classifications using proprietary classification algorithms. 2. Manually QC data classification 3. After completion of classification and final QC

approval, calculate final NVA, VVA, and density information for the project using ground control quality check points.

- 2022-07-01 00:00:00 - The NOAA Office for Coastal Management (OCM) downloaded 215 laz files from this USGS Rocky ftp site: <https://rockyweb.usgs.gov/vdelivery/Datasets/Staged/Elevation/LPC/Projects/>

OR\_McKenzieRiverCorridor\_Topobathy\_2021\_D21/OR\_MKRC\_Topobathy\_2021/LAZ/.

The data were in Oregon Lambert, NAD83(2011) Int feet coordinates with vertical elevation in NAVD88 (Geoid18) feet. Data were converted to geographic coordinates, from vertical feet to meters, to ellipsoid heights (using Geoid18), and elevations less than 0 were filtered out, for ingest into the NOAA Digital Coast Data Access Viewer.

The observed classes processed to the Data Access Viewer are: 1 = unclassified, 2 = ground, 7 = low noise, 9 = water, 17 = bridge deck, 18 = high noise, 40 = bathy bottom, 41 = water surface, 45 = water column.

**5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:**

**5.2. Quality control procedures employed (describe or provide URL of description):**

## **6. Data Documentation**

*The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.*

**6.1. Does metadata comply with EDMC Data Documentation directive?**

No

**6.1.1. If metadata are non-existent or non-compliant, please explain:**

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 5.2. Quality control procedures employed
- 7.1.1. If data are not available or has limitations, has a Waiver been filed?
- 7.4. Approximate delay between data collection and dissemination
- 8.3. Approximate delay between data collection and submission to an archive facility

**6.2. Name of organization or facility providing metadata hosting:**

NMFS Office of Science and Technology

**6.2.1. If service is needed for metadata hosting, please indicate:**

**6.3. URL of metadata folder or data catalog, if known:**

<https://www.fisheries.noaa.gov/inport/item/67489>

#### **6.4. Process for producing and maintaining metadata**

*(describe or provide URL of description):*

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: [https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC\\_PD-Data\\_Documentation\\_v1.pdf](https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf)

### **7. Data Access**

*NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.*

#### **7.1. Do these data comply with the Data Access directive?**

Yes

**7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?**

**7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:**

#### **7.2. Name of organization of facility providing data access:**

NOAA Office for Coastal Management (NOAA/OCM)

**7.2.1. If data hosting service is needed, please indicate:**

**7.2.2. URL of data access service, if known:**

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=9534/details/9534>

[https://rockyweb.usgs.gov/vdelivery/Datasets/Staged/Elevation/LPC/Projects/OR\\_McKenzieRiverCorri](https://rockyweb.usgs.gov/vdelivery/Datasets/Staged/Elevation/LPC/Projects/OR_McKenzieRiverCorri)

#### **7.3. Data access methods or services offered:**

Data is available online for bulk and custom downloads.

#### **7.4. Approximate delay between data collection and dissemination:**

**7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:**

### **8. Data Preservation and Protection**

*The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.*

**8.1. Actual or planned long-term data archive location:**

*(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)*

NCEI\_CO

**8.1.1. If World Data Center or Other, specify:**

**8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:**

**8.2. Data storage facility prior to being sent to an archive facility (if any):**

Office for Coastal Management - Charleston, SC

**8.3. Approximate delay between data collection and submission to an archive facility:**

**8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?**

*Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection*

Data is backed up to tape and to cloud storage.

**9. Additional Line Office or Staff Office Questions**

*Line and Staff Offices may extend this template by inserting additional questions in this section.*